

Hydrostatic Transmission Service, LLC
1644 Eason Blvd Bldg D
Tupelo, MS 38801
Toll: 800-361-0068 Phone (662) 680-8899 Fax (662) 680-8097



HYDROSTATIC-HYDRAULIC WARRANTY

HYDRAULIC-HYDROSTATIC WARRANTY INSTRUCTIONS

Hydrostatic Transmission Service, LLC warrants our hydraulic-hydrostatic repaired pump or motor to be free of any defects in workmanship for a period of one (1) year from the date of installation if the following conditions are met by the customer:

- A. The hydraulic-hydrostatic reservoir must be cleaned out with diesel fuel or solvent and clean rags, then blown out with air.
- B. All hydraulic-hydrostatic lines must be filled with diesel fuel or solvent and blown out backwards with air.
- C. All hydraulic-hydrostatic fittings must have replacement o-rings installed.
- D. The hydraulic-hydrostatic oil cooler must be removed from the machine and taken to a company that can adequately clean and core it out by certified a radiator shop. The oil cooler must be placed in vat and cored out, **do not** place in acid vat as fins are made of aluminum. After removing from vat, use cheese cloth on the bottom output and force naphtha or diesel from the top down with force to check again for any debris. Shake unit, if any rattling at all, purchase a new oil cooler **A copy of this receipt must be forwarded to our company so that we can put it on file.** High pressure hosing and/or flushing **does not** qualify for warranty procedure. *****IF THERE HAS BEEN CATASTROPHIC FAILURE AND/OR THE OIL COOLER CANNOT BE 100% CLEANED AND FREE OF DEBRIS, THEN THE OIL COOLER MUST BE REPLACED WITH A NEW OIL COOLER.*****
- E. All filters must be replaced.
- F. All hydraulic-hydrostatic oil must be replaced, preferably with a 30 weight non-foaming rust and oxide oil.
- G. The hydraulic-hydrostatic pump or motor must be physically charged with oil before connecting the hydraulic-hydrostatic lines back to the unit, by filling the cavity of the units up with a funnel and oil.
- H. Attach all lines, fill up reservoir with oil, start unit for 20 seconds and cut off. Then, refill with oil again.
- I. Any deviation from the above procedures will automatically void our warranty completely.
- J. If all the above conditions are met, we unconditionally warrant our product for one full year, parts only. This does not include labor to take off and put on.

I, the customer, have read and fully understand the above procedures and certify that all procedures have been completed as requested herein.

Customer or Company authorized personnel signature

Date

Customer or Company authorized personnel printed name

Title

Company Name

Invoice Number

****Signed, Dated Original Copy of this should be returned to Hydrostatic Transmission Service, LLC, Attn: Warranty Dept, 1644 Eason Blvd, Bldg D, Tupelo, MS 38801 or Email to info@hydrostatic-transmission.com**